

Electric Series Scissor Lifts

2732E

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

Model		(2732E)	
Dimensions			
Max Working Height		Metric	US
A Max Platform Height		10.1m	33'2"
B Max Horizontal Extension		8.1m	26'7"
C Length-Stowed		0.9m	3'
D Width-Stowed		2.46m	8'
Height-stowed	Rail Folded	1.96m	6'5"
	E Rail Unfolded	2.36m	7'9"
F Wheelbase		1.88m	6'2"
Ground Clearance (Pothole Guard Stowed)		0.1m	4"
Ground Clearance (Pothole Guard Deployed)		25mm	0.98"
Platform Dimensions(LxWxH)		2.30m×0.8m×1.1m (7'6.5"×2'7.5"×3'7")	
Performance			
Platform Allowable Occupants (Indoor/Outdoor)		2 persons/-	
Platform Capacity		250kg	551lbs
Drive Speed-Stowed		4km/h	2.5mph
Drive Speed-Raised		0.8km/h	0.5mph
Elevation Time(Unloaded)		30s-35s	
Descent Time(Unloaded)		34s-39s	
Gradeability		25%	
Turning Radius(Inside/Outside)		0/2.1m	
Tilt Rating(Front to Back/Side to Side)		3°/1.5°	
Tyres-solid		380×125mm(15×5")	
Power			
Batteries		6V×4/225Ah	
Power Source		24V DC	
Drive Mode		Motor, front-wheel	
Charger Input		100-240V AC	
Charger Output		30A	
Hydraulic System Capacity		15L	3.3gal
Weight			
Weight	2,090kg	4,608lbs	2,265kg 4,994lbs Indoor only
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR/KCS	

